

Performance		XATS 68 Kd	XAS 78 Kd	XAS 88 Kd	XAS 48 KdG	XAS 68 KdG
Working pressure	bar (g)	10	7	7	7	7
	psi (g)	150	100	100	100	100
Max. free air delivery	m³/min	3,5	4,5	5	2,5	3,5
	cfm	125	160	175	90	125
Output power	kVA	-	-	-	6,5   12	6,5   12
Max. ambient temperature at sea level	°C	50	50	50	50	50
Min. starting temperature / (cold start Aid)	°C	-10 / -20	-10 / -20	-10 / -20	-10 / -20	-10 / -20
Engine						
Model		KUBOTA V 1505 T	KUBOTA V 1505 T	KUBOTA V 1505 T	KUBOTA V 1505 (T)	KUBOTA V 1505 T
Number of cylinders		4	4	4	4	4
Power output @ normal shaft speed	kW	33	33	33	26,5 (33)	33
Nominal speed	rpm	3000	3000	3000	3000	3000
Unload speed	rpm	1850	1850	1850	1850	1850
Capacity						
Engine oil	l	5,5	5,5	5,5	5,5	5,5
Compressor oil	l	7,7	7,7	7,7	7,7	7,7
Fuel tank capacity	l	60	60	60	60	60
Noise level						
Sound power level (LwA)	dB(A)	98	98	98	98	98
Sound pressure level (LpA) at 7m	dB(A)	70	70	70	70	70
Dimensions and weight (box unit / undercarriage)						
Length	mm	1940 / 2290	1940 / 2290	1940 / 2290	1940 / 2290	1940 / 2290
Width	mm	1180 / 1350	1180 / 1350	1180 / 1350	1180 / 1350	1180 / 1350
Height	mm	1150 / 1400	1150 / 1400	1150 / 1400	1150 / 1400	1150 / 1400
Weight (box / portable)	kg	650 / <750	650 / <750	650 / <750	650 / <750	650 / <750

## ISO STANDARDS

Atlas Copco's fully implemented Quality Management and Environmental Management systems in the design and manufacturing of these units fulfill the requirements of ISO 9001 and ISO 14001 & OHSAS 18001. The range has also been given the certificate tested according to ISO 1217:2009-annex D.

